

- (A) SOL A GRY
- (B) SOL B BLU
- (C) SOL C GRY/WHT
- (D) SOL D VIO
- (E) SOL E VIO/WHT
- (F) SOL F GRN
- (G) SOL G GRN/YEL
- (H) SOL H PINK

8' TO EXIT JUNCTION

HPD26-24-23SE-L015

(W) GND BLK

(L) CONV LOCK WHT/BLK

(T) TEMP ORG


(U) TEMP BLK/WHT

(R) WHT/GRN

(S) RPM SENSOR WHT/GRN

TWIST


22-18S




Cable Clamp #714-2564
ALLIED # 605-7091 TYPE 3108B 90°

SPLIT 18"

Cable Clamp #714-2564
ALLIED # 605-7203 TYPE 3108B 90°



HOBBS PN76074
PRESSURE SWITCH 60PSI




3 FEET FROM EXIT

3 FEET FROM EXIT

TRANS TEMP

ISSPRO 3959-03

MAG PICKUP
2 FEET FROM EXIT



ALLIED 714-4004
MS3106A-10SL-4S
CLAMP 714-2560

LOCK B,C,D,F
NEUTRAL ALL SOL OFF

- #1 F,H
- #2 G,H
- #3 C,F
- #4 D,F
- #5 C,G
- #6 D,G
- #7 E,F

DWG#: X275	DWG NAME: HARNESS, TRANS ALLISON 9800	DATE: 07/31/06
File: C:\X275\X275HNS TRANS ALLISON 9800	Dwg. By:	
Dwg Not to Scale	Revisions 0	Whitlock Instrument 1300 N. Texas Odessa, Tx 79761 WEB SITE: noflo.com CONTACT: LARRY RITCHIE 432-337-3412 FAX: 432-335-5926 larry@noflo.com
W.I.Part#	Num. Date:	
Material:		
Tolerance:		